

FPS WASA 14

SDS Number: 60408

Revision Date: 7/24/2015

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Product Name: FPS WASA 14
Revision Date: 7/24/2015
SDS Number: 60408
CAS Number: Blend
Product Code: 60408
Synonyms: Diesel Fuel Additive

Company Identification

Manufactured for:
Fuel Performance Solutions
P.O. Box 903
Chesterton, IN 46304 USA

1-888-577-3935 (For product information)
1-800-424-9300 (For emergencies)
1-800-424-9300 or 1-703-527-3887 (CHEMTREC)

2 HAZARDS IDENTIFICATION

GHS Signal Word:
DANGER

GHS Hazard Pictograms:



GHS Classifications:

Physical, Flammable Liquids, 3
Health, Specific target organ toxicity - Single exposure, 3
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Skin corrosion/irritation, 2
Health, Acute toxicity, 4 Inhalation
Health, Aspiration hazard, 1
Health, Carcinogenicity, 2
Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Phrases:

H226 - Flammable liquid and vapor
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H319 - Causes serious eye irritation
H315 - Causes skin irritation
H332 - Harmful if inhaled
H304 - May be fatal if swallowed and enters airways
H351 - Suspected of causing cancer
H411 - Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

FPS WASA 14

SDS Number: 60408

Revision Date: 7/24/2015

Page 2 of 5

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P302+352 - IF ON SKIN: Wash with soap and water.
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.
Continue rinsing.
P273 - Avoid release to the environment.

3**COMPOSITION/INFORMATION ON INGREDIENTS****Ingredients:**

Chemical Name	Percentage	CAS#
Light aromatic solvent naphtha	25.0 - 35.0	64742-95-6
1,2,4-Trimethylbenzene	< 20.0	95-63-6
Heavy aromatic solvent naphtha	10.0 - 15.0	64742-94-5
Dipropylene glycol methyl ether	< 10.0	34590-94-8
2-Ethylhexanol	< 10.0	104-76-7
Xylene	< 3.0	1330-20-7
Naphthalene	< 2.0	91-20-3
1,3,5-Trimethylbenzene	< 1.0	108-67-8
Trimethylbenzene	< 1.0	25551-13-7
Ethylbenzene	< 1.0	100-41-4
Cumene	< 1.0	98-82-8
Vinyl acetate monomer	< 0.1	108-05-4

4**FIRST AID MEASURES**

Inhalation: If symptoms develop, move victim to fresh air.
If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water.
Remove contaminated clothing and wash before reuse.
Get medical attention if needed.

Eye Contact: Flush with water for several minutes.
If effects occur, consult a physician.

Ingestion: Rinse mouth with water and drink 2-4 cups of water.
Get immediate medical attention.

Note to Physician:
Activated charcoal may be administered.

FPS WASA 14

SDS Number: 60408

Revision Date: 7/24/2015

Page 3 of 5

5 FIRE FIGHTING MEASURES

Flash Point: 42.2 C (108.0 F)
Flash Point Method: PMCC

Use dry powder, foam, or carbon dioxide fire extinguishers.
Water may be ineffective unless used by experienced fire fighters.

6 ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition - Heat, sparks, flame, and electricity
Contain spilled material.
Collect in suitable and properly labeled containers.
Pick up excess with inert absorbant material
Keep away from drains and ground water.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Keep away from sources of ignition.
Do not pressurize, cut, weld, braze, solder, drill, or grind containers.
Handle with care and avoid spillage on the floor (slippage).
Ground and bond containers when transferring material

Storage Requirements: Keep away from sources of ignition.
Store in a tightly closed container

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equip: Use of safety glasses and gloves are recommended.

EXPOSURE GUIDELINES: **LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)**

OSHA TWA: 500 ppm

1,2,4-TRIMETHYLBENZENE

ACGIH TWA: 25 ppm

DIPROPYLENE GLYCOL METHYL ETHER

OSHA PEL: 100 ppm, 600 mg/m³

ACGIH TWA: 100 ppm

ACGIH STEL: 150 ppm

XYLENE

OSHA TWA: 100 ppm, 435 mg/m³

ACGIH TWA: 100 ppm, 434 mg/m³

OSHA STEL: 150 ppm, 655 mg/m³

ACGIH STEL: 150 ppm, 651 mg/m³

NAPHTHALENE

OSHA PEL: 10 ppm, 50 mg/m³

OSHA TWA: 10 ppm, 50 mg/m³

ACGIH TWA: 10 ppm, 52 mg/m³

OSHA STEL: 15 ppm, 75 mg/m³

FPS WASA 14

SDS Number: 60408

Revision Date: 7/24/2015

Page 4 of 5

ACGIH STEL: 15 ppm, 79 mg/m³

TRIMETHYLBENZENE

OSHA TWA: 25 ppm, 125 mg/m³

ACGIH TWA: 25 ppm, 123 mg/m³

CUMENE

OSHA PEL: 50 ppm

OSHA TWA: 50 ppm, 245 mg/m³

ACGIH TWA: 50 ppm, 246 mg/m³

1,3,5-TRIMETHYLBENZENE

ACGIH TWA: 25 ppm

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber	Solubility:	Nil in water
Physical State:	Liquid		
Spec Grav./Density:	< 1.0 (Water = 1)		

10 STABILITY AND REACTIVITY

Stability:	Product is stable under normal conditions.
Conditions to Avoid:	High temperatures above 50 C (122 F) and open flame.
Materials to Avoid:	Avoid strong oxidizing agents. May burn or react violently to flourine/oxygen mixtures.

11 TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.
No component is listed as a carcinogen, mutagen, or teratogen.

SKIN EFFECTS:

Solvent Petroleum Naphtha, no deaths reported at 4 ml/kg (Rat). Slightly irritating (rabbit, 4 hour(s)).
Vinyl Acetate Monomer, Skin absorption LD50 is 2,335 mg/kg in rabbits.

ACUTE ORAL EFFECTS:

Solvent Petroleum Naphtha, LD50, 10 ml/kg in rats.
Oral LD 50 for Vinyl Acetate Monomer is 2,920 mg/kg in rats.
Naphthalene, Oral LD50, 2600 mg/kg (rat).

ACUTE INHALATION EFFECTS:

Solvent Petroleum Naphtha, no deaths at 710 ppm (v) (Rat) 4 Hour (s).
Vinyl Acetate Monomer, four hour inhalation LC50 is 4,000 ppm in rats.

12 ECOLOGICAL INFORMATION

Avoid exposing to the environment, no specific aquatic data available

FPS WASA 14

SDS Number: 60408

Revision Date: 7/24/2015

Page 5 of 5

13 DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all local, state/provincial, and national requirements
Do not flush to surface water or drains

14 TRANSPORT INFORMATION

UN #: NA 1993, Class: -, Proper Shipping Name: Combustible liquid, n.o.s.

This material is not regulated for US DOT transportation in quantities less than 119 Gallons.

If shipping overseas, or via air, the proper shipping name is: Flammable liquid, n.o.s., (Contains Petroleum Naphtha, 1,2,4-Trimethylbenzene), 3, UN1993, PGIII.

15 REGULATORY INFORMATION

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16 OTHER INFORMATION

The information contained in this Safety Data Sheet relates only to the specific material designated. Fuel Performance Solutions assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Fuel Performance Solutions.