



FPS™

Premium High Mileage + Cetane

DIESEL FUEL ADDITIVE

FUEL PERFORMANCE SOLUTIONS

FPS Premium High Mileage + Cetane is specifically formulated for use in all types of diesel fuel, including Ultra Low Sulfur Diesel (ULSD) and Biodiesel blends. It is an ashless, multi-functional additive that provides significant, money-saving performance benefits when used as recommended.

Fuel Economy

- ✓ NEW High Pressure Common Rail Detergent to prevent sticking injectors.
- ✓ Contains a high level of detergency to aggressively clean up injectors, which improves fuel economy performance up to 5.0%.
- ✓ Prevents loss of engine power resulting from incomplete combustion of fuel.
- ✓ Passes Peugeot DW-10 test for injector clean up performance.

Reduces Filter Plugging

- ✓ ASTM D2068 proves Biodiesel and ULSD filter plugging is reduced by 39.7%.
- ✓ Decreases Asphaltene plugging by 14.9%.

Cetane Increase

- ✓ Improves ignition quality. Faster and more complete combustion.
- ✓ Less crank time to reduce starter wear and increase battery life.
- ✓ Consistently moves cetane levels up 2 points or more.
- ✓ Reduces misfire conditions.
- ✓ Better cold starting & quicker warm ups.

Lubricity

- ✓ Increases lubricity - especially beneficial when using ULSD, giving protection against wear for injectors, fuel pumps, upper cylinders, rings and valve train.
- ✓ Exceeds lubricity standard in ASTM D 975 as well as the stringent Engine Manufacturers Association (EMA) specification.

Emissions

- ✓ Reduces black smoke by up to 93%.
- ✓ Decreases NOx, carbon monoxide and particulate matter emissions.

Stability & Moisture Control

- ✓ Increases storage stability and delays oxidation.
- ✓ Decreases risk of thermal degradation of fuel.
- ✓ Gradually removes water from storage tanks.

Recommended Treatment Ratio:

One gallon of **FPS Premium High Mileage + Cetane** treats 2500 gallons of diesel fuel.

Double the dose for the first fueling to clean up injectors, then use at a ratio of 1:2500.

Package

Sizes:

- 2.5-gal Jug;
- 55-gal Drum;
- Bulk Tote



www.FPSadditive.com

1-888-577-FUEL (3835)

The sulfur content of this additive does not exceed 15 PPM.